

We claim:

1. A discharge lamp comprising a ceramic discharge vessel enclosing a discharge space, said discharge vessel including within said discharge space an ionizable material comprising a metal halide, a first and second discharge electrode feedthrough means, and a first and second current conductor connected to said first and second discharge electrode feedthrough means, respectively;

said lamp having a power range of about 150W to about 1000W and exhibiting one or more of a characteristic selected from the group consisting of a CCT (correlated color temperature) of about 3800 to about 4500K, a CRI (color rendering index) of about 70 to about 95, a MPCD (mean perceptible color difference) of about +10, and a luminous efficacy up to about 85-95 lumens/watt.

2. A lamp as claimed in Claim 1 retrofit with ballasts and lighting fixtures designed for high pressure sodium or quartz metal halide lamps.

3. A discharge lamp having a power range of about 150W to about 1000W and comprising a ceramic discharge vessel enclosing a discharge space, said discharge vessel including within said discharge space an ionizable material comprising a metal halide, a first and second discharge electrode feedthrough means, and a

first and second current conductor connected to said first and second discharge electrode feedthrough means, respectively;

wherein the ceramic discharge vessel includes an arc tube comprising:

5 a cylindrical barrel having a central axis and a pair of opposed end walls,

a pair of ceramic end plugs extending from respective end walls along said axis,

10 a pair of lead-ins extending through respective end plugs, said lead-ins being connected to respective electrodes which are spaced apart in said central barrel,

wherein the electrode feedthrough means each have a lead-in of niobium which is hermetically sealed into the arc tube, a central portion of molybdenum/aluminum cermet, a molybdenum rod 15 portion and a tungsten rod having a winding of tungsten.

4. A lamp as claimed in Claim 3, wherein the arc tube has a molybdenum coil attached to its surface.

20 5. A lamp as claimed in Claim 4, wherein the discharge space contains an ionizable filling of an inert gas, a mixture of metal halide, and mercury.

6. A lamp as claimed in Claim 5 wherein, said discharge vessel

has a ceramic wall and is closed by a ceramic plug, said electrode feedthrough means including at least one tungsten electrode which is connected to a niobium electric current conductor by means of a leadthrough element which projects into the ceramic plug with a tight fit, is connected thereto in a gastight manner by means of a sealing ceramic and has a part formed from aluminum oxide and molybdenum which forms a cermet at the area of the gastight connection.

10 7. A lamp as claimed in Claim 5, wherein, said discharge vessel has a ceramic wall and is closed by a ceramic plug, said electrode feedthrough means including at least one tungsten electrode which is connected to a niobium electric current conductor by means of a leadthrough element which projects into the ceramic plug with a tight fit, is connected thereto in a gas-tight manner by means of a sealing ceramic and has a first part formed from aluminum oxide and molybdenum which forms a cermet at the area of the gas-tight connection and a second part which is a metal part and extends from the cermet in the direction of the electrode.

8. A lamp as claimed in Claim 7, wherein the metal part is a molybdenum rod.

9. A lamp as claimed in Claim 5, wherein the arc tube has an aspect ratio (IL/ID) in the range of about 3.3 to about 6.2.

10. A lamp as claimed in Claims 6 and 7, wherein the electrode has a tip extension in the range of about 0.2 to about 1.0mm; the cermet contains at least about 35 wt.% Mo with the remainder being  $\text{Al}_2\text{O}_3$ , and the sealing ceramic flow completely covers the Nb connector.

11. A lamp as claimed in Claim 10, wherein the arc tube and the electrode feedthrough means have the following characteristics for a given lamp power:

Power	IL	ID	IL/ID	Wall	Wall	Rod	Rod
W	mm	mm	Aspect	Loading	Thickness	Diameter	Length
			Ratio, mm	W/cm <sup>2</sup>	mm	mm	mm
150	26-32	5-7	3.3-6.2	20-35	0.8-1.1	0.4-0.6	3-6
200	27-32	6.5-7.5	3.3-6.2	25-30	0.85-1.2	0.4-0.6	4-8
250	28-34	7.5-8.5	3.3-6.2	25-35	0.9-1.3	0.7-1.0	6-10
300	30-36	8-9	3.3-6.2	25-37	0.92-1.4	0.7-1.0	6-10
350	33-40	8.5-10	3.3-6.2	24-40	0.98-1.48	0.7-1.1	6-11
400	36-45	8.5-11	3.3-6.2	22-40	1.0-1.5	0.7-1.1	6-11

12. A lamp as claimed in Claim 11, wherein said metal halide mixture comprises the following salts of 6-25 wt%  $\text{NaI}$ , 5-6 wt%  $\text{TlI}$ , 34-37 wt%  $\text{CaI}_2$ , 11-18 wt%  $\text{DyI}_3$ , 11-18 wt%  $\text{HoI}_3$ , and 11-18 wt%  $\text{TmI}_3$ .

13. A lamp as claimed in Claim 12, wherein the ionizable filling is a mixture of about 99.99% of Xenon and a trace amount of <sup>85</sup>Kr radioactive gas.

5 14. A lamp as claimed in Claim 12, wherein the ionizable filling is a mixture of Argon and/or Krypton, Xenon, and a trace amount of <sup>85</sup>Kr radioactive gas.

10 15. A lamp as claimed in Claim 12, wherein the ionizable filling is Xenon and/or Krypton.

15 16. A lamp as claimed in Claim 1, 5, and 13, having a power range of about 150W to about 1000W and nominal voltage of 100V to 260V, and one or more of the following characteristics: a lumen maintenance of >80%, a color temperature shift <200K from 100 to 10,000 hours, and lifetime of about 10,000 to about 25,000 hours.

20 17. A design space of parameters for the design and construction of a discharge lamp having a power range of about 150W to about 1000W and comprising a ceramic discharge vessel enclosing a discharge space, said discharge vessel including within said discharge space an ionizable material comprising a metal halide mixture, a first and second discharge electrode feedthrough means, and a first and second current conductor connected to said  
25 first and second discharge electrode feedthrough means, respectively;

said design space including at least one of the following parameters :

(i) the arc tube length, diameter and wall thickness limits of said discharge lamp correlated to and expressed as functions of lamp power, and/or color temperature, and/or lamp voltage; and

(ii) the electrode feedthrough structure limits used to conduct electrical currents with minimized thermal stress on the arc tube correlated to and expressed as a function of lamp current.

10 18. A design space as claimed in Claim 17, wherein said parameters also include:

(i) a general aspect ratio of the inner length (IL) to the inner diameter (ID) of the arc tube body is higher than that of ceramic metal halide lamps having a power of less than about 150W;

15 (ii) the upper and lower limits of electrode rod diameter correlated to and expressed as a function of lamp current; and

(iii) a composition range of the salts correlated to color temperature and lamp voltage.

20 19. A design space as claimed in Claim 18, wherein said design parameters include the following characteristics for the design of an arc tube and electrode feedthrough means for a given lamp power:

Power	IL	ID	IL/ID	Wall	Wall	Rod	Rod
W	mm	mm	Aspect	Loading	Thickness	Diameter	Length
			Ratio, mm	W/cm <sup>2</sup>	mm	mm	mm
150	26-32	5-7	3.3-6.2	20-35	0.8-1.1	0.4-0.6	3-6
200	27-32	6.5-7.5	3.3-6.2	25-30	0.85-1.2	0.4-0.6	4-8
250	28-34	7.5-8.5	3.3-6.2	25-35	0.9-1.3	0.7-1.0	6-10
300	30-36	8-9	3.3-6.2	25-37	0.92-1.4	0.7-1.0	6-10
350	33-40	8.5-10	3.3-6.2	24-40	0.98-1.48	0.7-1.1	6-11
400	36-45	8.5-11	3.3-6.2	22-40	1.0-1.5	0.7-1.1	6-11

15 (20) A method for the design and construction of a discharge lamp  
 having a power range of about 150W to about 1000W and comprising  
 a ceramic discharge vessel enclosing a discharge space, said  
 discharge vessel including within said discharge space an  
 ionizable material comprising a metal halide mixture, a first and  
 20 second discharge electrode feedthrough means, and a first and  
 second current conductor connected to said first and second  
 discharge electrode feedthrough means respectively;  
 which method comprises the steps of determining the dimensions of  
 the arc tube of the discharge vessel and the electrode  
 25 feedthrough means structure using a design space of Claim 17.

21. A method for the design and construction of a discharge lamp  
 having a power range of about 150W to about 1000W and comprising  
 a ceramic discharge vessel enclosing a discharge space, said  
 30 discharge vessel including within said discharge space an  
 ionizable material comprising a metal halide mixture, a first and  
 second discharge electrode feedthrough means, and a first and  
 second current conductor connected to said first and second

discharge electrode feedthrough means, respectively;

which method comprises the steps of determining the dimensions of the arc tube of the discharge vessel and the electrode feedthrough means structure using a design space of Claim 18.

5

22. A method for the design and construction of a discharge lamp having a power range of about 150W to about 1000W and comprising a ceramic discharge vessel enclosing a discharge space, said discharge vessel including within said discharge space an

10 ionizable material comprising a metal halide, a first and second discharge electrode feedthrough means, and a first and second current conductor connected to said first and second discharge electrode feedthrough means, respectively;

COPIES OF DOCUMENT

15

which method comprises the steps of determining the dimensions of the arc tube of the discharge vessel and the electrode feedthrough means structure using a design space of Claim 19.

20

23. A method as claimed in Claim 22, including the further design parameter that the metal halide comprises the following salts of 6-25 wt% NaI, 5-6 wt% TlI, 34-37 wt% CaI<sub>2</sub>, 11-18 wt% DyI<sub>3</sub>, 11-18 wt% HoI<sub>3</sub>, and 11-18 wt% TmI<sub>3</sub>.

25

24. A method as claimed in Claim 23, including the further design parameter that the ionizable filling is a mixture of about 99.99% of Xenon and a trace amount of <sup>85</sup>Kr radioactive gas.

25. A method as claimed in Claim 24, including the further design parameter that the discharge vessel has a ceramic wall and is



closed by a ceramic plug, said electrode feedthrough means including at least one tungsten electrode which is connected to a niobium electric current conductor by means of a leadthrough element which projects into the ceramic plug with a tight fit, is  
5 connected thereto in a gas-tight manner by means of a sealing ceramic and has a part formed from aluminum oxide and molybdenum which forms a cermet at the area of the gas-tight connection.

26. A method as claimed in Claim 24, including the further design  
10 parameter that the discharge vessel has a ceramic wall and is closed by a ceramic plug, said electrode feedthrough means including at least one tungsten electrode which is connected to a niobium electric current conductor by means of a leadthrough  
15 element which projects into the ceramic plug with a tight fit, is connected thereto in a gas-tight manner by means of a sealing ceramic and has a first part formed from aluminum oxide and molybdenum which forms a cermet at the area of the gas-tight connection and a second part which is a metal part and extends from the cermet in the direction of the electrode.

20 27. A method as claimed in Claim 26, wherein the metal part is a molybdenum rod.

28. A method as claimed in Claims 25 and 26, wherein the

electrode has a tip extension in the range of about 0.2 to about 1.0mm; the cermet contains at least about 35 wt.% Mo with the remainder being  $\text{Al}_2\text{O}_3$ , and the sealing ceramic flow completely covers the Nb connector.

5

29. A method as claimed in Claim 20 wherein the lamp produced has a power range of about 150W to about 1000W and nominal voltage of 100V to 260V, and one or more of the following characteristics: a lumen maintenance of >80%, a color temperature shift <200K from 100 to 8,000 hours, and lifetime of about 10,000 to about 25,000 hours.

10

NO  
RECEIVED  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

*Cell  
A3*

15

20